SIGMA-ALDRICH

Material Safety Data Sheet

Version 3.14 Revision Date 04/27/2012 Print Date 05/30/2012

1. PRODUCT AND COMPANY II	1. PRODUCT AND COMPANY IDENTIFICATION				
Product name	:	Acetaldehyde			
Product Number Brand	:	00070 Fluka			
Supplier	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA			
Telephone	:	+1 800-325-5832			
Fax	:	+1 800-325-5052			
Emergency Phone # (For both supplier and manufacturer)	:	(314) 776-6555			
Preparation Information	:	Sigma-Aldrich Corporation Product Safety - Americas Region 1-800-521-8956			

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid, Carcinogen, Target Organ Effect, Harmful by ingestion., Skin sensitiser, Irritant

Target Organs

Blood, Kidney, Lungs, Cardiovascular system., Liver, Central nervous system

Other hazards which do not result in classification

May form explosive peroxides.Lachrymator., Photosensitizer.

GHS Classification

Flammable liquids (Category 1) Acute toxicity, Oral (Category 4) Acute toxicity, Inhalation (Category 5) Acute toxicity, Dermal (Category 5) Skin irritation (Category 3) Serious eye damage (Category 1) Skin sensitization (Category 1) Carcinogenicity (Category 2) Specific target organ toxicity - single exposure (Category 3) Acute aquatic toxicity (Category 3)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H224	Extremely flammable liquid and vapour.
H302	Harmful if swallowed.
H313 + H333	May be harmful in contact with skin or if inhaled.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.

H318 H335 H351 H402	Causes serious eye damage. May cause respiratory irritation. Suspected of causing cancer. Harmful to aquatic life.
Precautionary statement(s P210 P261 P280 P305 + P351 + P338) Keep away from heat/sparks/open flames/hot surfaces No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wear protective gloves/ eye protection/ face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
HMIS Classification Health hazard: Chronic Health Hazard: Flammability: Physical hazards:	2 * 4 2
NFPA Rating Health hazard: Fire: Reactivity Hazard:	2 4 0
Potential Health Effects	
Inhalation Skin Eyes Ingestion	May be harmful if inhaled. Causes respiratory tract irritation. Harmful if absorbed through skin. Causes skin irritation. Causes eye irritation. Harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms	: Ethanal	:	
Formula Molecular Weight	: C ₂ H ₄ O : 44.05 g/mol		

Component		Concentration
Acetaldehyde		
CAS-No.	75-07-0	-
EC-No.	200-836-8	
Index-No.	605-003-00-6	

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical

May explode when heated. Closed containers may rupture and explode during runaway polymerization. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature: 2 - 8 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis	
Acetaldehyde	75-07-0	С	25 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Remarks	Eye & Uppe humans	r Respirate	ory Tract irritation Confirmed animal carcinogen with unknown relevance to		
		TWA	100 ppm 180 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		STEL	150 ppm 270 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		TWA	200 ppm 360 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
	The value in	mg/m3 is	approximate.	·	

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Immersion protection Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: > 480 min Material tested:Butoject® (Aldrich Z677647, Size M)

Splash protection Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: > 30 min Material tested:Butoject® (Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 873000, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

••	
Form	liquid, clear
Colour	colourless
Safety data	
рН	5 at 20 °C (68 °F)
Melting point/freezing point	Melting point/range: -125 °C (-193 °F) - lit.
Boiling point	21 °C (70 °F) - lit.
Flash point	-40 °C (-40 °F) - closed cup
Ignition temperature	175 °C (347 °F)
Autoignition	no data available

temperature	
Lower explosion limit	4 %(V)
Upper explosion limit	60 %(V)
Vapour pressure	1,008.5 hPa (756.4 mmHg) at 20 °C (68 °F) 1,451 hPa (1,088 mmHg) at 30 °C (86 °F) 2,660 hPa (1,995 mmHg) at 55 °C (131 °F)
Density	0.785 g/cm3 at 25 °C (77 °F)
Water solubility	completely miscible
Partition coefficient: n-octanol/water	log Pow: 0.5
Relative vapour density	1.52 - (Air = 1.0)
Odour	no data available
Odour Threshold	no data available
Evaporation rate	no data available

10. STABILITY AND REACTIVITY

Chemical stability

Avoid exposure to air any longer than necessary so as to prevent peroxide formation. Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Air

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid

Oxidizing agents, Reducing agents, acids, Nitric acid, Peroxides, Bases, Sodium Hydroxide, Amines, Ammonia, Oxygen, Warning: acetaldehyde is oxidized rapidly and exothermically by air, to acetic acid, Acid anhydrides, Alcohols, Halogens, Ketones, Phenol, Hydrogen sulfide gas, Hydrogen peroxide

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - 661 mg/kg Remarks: Peripheral Nerve and Sensation:Spastic paralysis with or without sensory change. Behavioral:Altered sleep time (including change in righting reflex). Lungs, Thorax, or Respiration:Dyspnea.

Inhalation LC50

LC50 Inhalation - rat - 4 h - 13300 ppm Remarks: Behavioral:Excitement. Lungs, Thorax, or Respiration:Dyspnea.

Dermal LD50

LD50 Dermal - rabbit - 3,540 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation Skin - rabbit - Mild skin irritation

Serious eye damage/eye irritation

Eyes - rabbit - Severe eye irritation

Respiratory or skin sensitization

May cause allergic skin reaction.

Photosensitizer.

Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects.

Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Acetaldehyde)
- NTP: Reasonably anticipated to be a human carcinogen (Acetaldehyde)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System) May cause respiratory irritation.

Specific target organ toxicity - repeated exposure (Globally Harmonized System) no data available

Aspiration hazard no data available

Potential health effects

Inhalation	May be harmful if inhaled. Causes respiratory tract irritation.
Ingestion	Harmful if swallowed.
Skin	Harmful if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.

Signs and Symptoms of Exposure

Blurred vision, Unconsciousness, Headache, Vomiting, Nausea, Pulmonary edema. Effects may be delayed., Convulsions, sneezing, Cough, Shortness of breath

Synergistic effects no data available

Additional Information RTECS: AB1925000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) - 31 mg/l - 96 h

LC100 - Leuciscus idus (Golden orfe) - 124 - 156 mg/l - 48 h

EC50 - Daphnia magna (Water flea) - 48 mg/l - 48 h

Toxicity to daphnia and other aquatic invertebrates

Persistence and degradability no data available

Bioaccumulative potential no data available

Mobility in soil no data available

PBT and vPvB assessment no data available

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UI Pr Re M	N number: 1089 Class: 3 oper shipping name: Acetaldehyde eportable Quantity (RQ): 1000 lbs arine pollutant: No pison Inhalation Hazard: No	Packing group: I	
UI Pr	IDG N number: 1089 Class: 3 roper shipping name: ACETALDEHYDE arine pollutant: No	Packing group: I	EMS-No: F-E, S-D
UI Pr	TA N number: 1089 Class: 3 oper shipping name: Acetaldehyde TA Passenger: Not permitted for transport	Packing group: I	

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Carcinogen, Target Organ Effect, Harmful by ingestion., Skin sensitiser, Irritant

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

75-07-0

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313: CAS-No. Revision Date

Acetal	Idehvd	P
7100101		

Fluka - 00070

2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Acetaldehyde	CAS-No. 75-07-0	Revision Date 2007-07-01
Pennsylvania Right To Know Components	CAS-No.	Revision Date
Acetaldehyde	75-07-0	2007-07-01
New Jersey Right To Know Components	CAS-No.	Revision Date
Acetaldehyde	75-07-0	2007-07-01
California Prop. 65 Components WARNING! This product contains a chemical known to the State of California to cause cancer. Acetaldehyde	CAS-No. 75-07-0	Revision Date 2007-09-28

16. OTHER INFORMATION

Further information

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.